

GENSET MODEL PCG320

POWERPAC	CUMMINS	380-415 50hz		480v 60hz	
Generating Set Model	Engine Model	KVA	KW	KVA	KW
PCG320 (Prime)	NT855G6	320	256	325	260
PCG320 (Standby)	NT855G6	350	280	356	285

ALTERNATOR MODELS

Newage Stamford	Mecc Alte	Leroy Somer
HCI444E	ECO38-3LN	LSA47.2VS2

CONTROL PANEL

DEEPSEA	SMARTGEN
DSE7320	HGM9320CAN

RATINGS:

- Prime Output:**
 This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for one hour in 12 hours.
- Standby Output:**
 This rating is applicable for supplying electrical power (at variables load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard References Conditions:**
 25°C, 100ml A.S.L, 30% relative humidity.

Design Features:

- High Quality assembly, providing stiffness and low vibration.
- Powder coated steel, Corrosion and scratch resistant.
- Compact and long service life.
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month Warranty.

Design Standards:

- CE marking
- ISO8528-1995
- GB/T2820-1997
- ISO 9001:2008 Registered Company



CONFIGURATION:

- 4-Stroke water-cooled diesel engine
- Industrial silencer
- Coolant recovery tank
- Single bearing, 4 pole brushless alternator
- Anti vibration mounting
- Integral fuel tank with fully bounded base protection
- Fuel level sensor
- Control Panel - DEEPSEA/SMARTGEN
- Auto start control system with electronic digital control module DSE6020 as standard
- Output circuit breaker
- Emergency stop button
- High engine temprature and low oil pressure shutdown system
- 12V starter battery with leads and switch

TROLLY:

- 4 Wheel Trolley Mounted
- Steerable
- Towable
- Having Brake

AUCOUSTIC CANAOPY FEATURES:

- Water and dust proof design
- Door locks
- High quality sound absorbing and fire retardant inner material
- Lifting lugs
- Forklift holes in base